CHI MEI
OPTOELECTRONICS CORP.

Issued Date: SEP, 22, 2008
Model No.: V260B1-PN1

Approval

TFT LCD Approval Specification

MODEL NO.: V260B1 – PN1

Customer: _____

Approved by: _____

Note:

Approved By	TV Head Division
	LY Chen

Reviewed By	QRA Dept.	Product Development Div.
	Tomy Chen	WT Lin

Prepared By	LCD TV Marketing and Product Management Div.	
	WY Li	Chloe Chen

1

Version 2.1

Approval

- CONTENTS -

Version 2.1

Issued Date: 22, SEP 2008
Model No.: V260B1   - PN1

Approval

REVISION HISTORY

Version	Date	Page (New)	Section	Description
Ver 2.0	Jun. 23,'08	All	All	Tentative Specification was first issued.
Ver 2.1	Sep. 29,'08	19	9.2	Add a spacer below the panel.

3

Version 2.1

Issued Date: 22, SEP 2008
Model No.: V260B1　- PN1

Approval

1. GENERAL DESCRIPTION

1.1 OVERVIEW

V260B1- PN1 is a 26-inch TFT LCD cell with driver ICs and RSDS interface. This module supports 1366 x 768 WXGA format and can display 16.2M colors (6-bit+FRC colors). The backlight unit is not built in.

1.2 CHARACTERISTICS

CHARACTERISTICS ITEMS	SPECIFICATIONS
Screen Diagonal　[in]	26.0
Pixels　[lines]	1366×768
Active Area　[mm]	575.769×323.712
Sub -Pixel Pitch　[mm]	0.1405(H)×0.4215(V)
Pixel Arrangement	RGB vertical stripe
Weight　[g]	TYP. 1000
Physical Size　[mm]	592(W) x 339.8(H) x 1.84(D) Typ.
Display Mode	TN, Normally White
Contrast Ratio	800:1 Typ. (Typical value measured at CMO's module)
Glass thickness (Array/CF)　[mm]	0.7 / 0.7
Viewing Angle (CR>20)	+80/-80(H), +80/-70(V) Typ. (Typical value measured at CMO's module)
Color Chromaticity	R=(0.650, 0.328) G=(0.274,0.583) B=(0.150,0.094) W=(0.314,0.331) *Please refer to "color chromaticity" on p.12
Cell Transparency　[％]	6.2%Typ. (Typical value measured at CMO's module)
Polarizer (CF side)	Anti-Glare coating, 587.4(H) x 335.2(w). Hardness: 3H
Polarizer (TFT side)	587.4(H) x 335.2(w), Hardness: 3H

1.3 MECHANICAL SPECIFICATIONS

Item	Min.	Typ.	Max.	Unit	Note
Weight		840		g	
I/F connector mounting position	The mounting inclination of the connector makes the screen center within ±0.5mm as the horizontal.				(2)

Note (1) Please refer to the attached drawings for more information of front and back outline dimensions.

(2) Connector mounting position

+/- 0.5mm

4

Version 2.1

Issued Date: 22, SEP 2008
Model No.: V260B1   - PN1

Approval

2. ABSOLUTE MAXIMUM RATINGS

2.1 ABSOLUTE RATINGS OF ENVIRONMENT

Item	Symbol	Value		Unit	Note
		Min.	Max.		
Storage Temperature	T_{ST}	-20	+60	ºC	(1), (3)
Operating Ambient Temperature	T_{OP}	0	50	ºC	(1), (2), (3)
Altitude Operating	A_{OP}	0	5000	M	(3)
Altitude Storage	A_{ST}	0	12000	M	(3)

Note (1) Temperature and relative humidity range is shown in the figure below.

(a) 90 %RH Max. (Ta $\leq$ 40 ºC).

(b) Wet-bulb temperature should be 39 ºC Max. (Ta > 40 ºC).

(c) No condensation.

Relative Humidity (%RH)

Temperature (ºC)

Note (2) The maximum operating temperature is based on the test condition that the surface temperature of display area is less than or equal to 65 ºC with LCD module alone in a temperature controlled chamber. Thermal management should be considered in your product design to prevent the surface temperature of display area from being over 65 ºC. The range of operating temperature may degrade in case of improper thermal management in your product design.

Note (3) The rating of environment is base on LCD module. Leave LCD cell alone, this environment condition can't be guaranteed. Except LCD cell, the customer has to consider the ability of other parts of LCD module and LCD module process.

Version 2.1

Approval

2.2 ABSOLUTE RATINGS OF ENVIRONMENT (OPEN CELL)

Storage Condition : With shipping package.

Storage temperature range : 25±5 ℃

Storage humidity range : 50±10%RH

Shelf life : a month

2.3 ELECTRICAL ABSOLUTE RATINGS (OPEN CELL)

Item	Symbol	Value		Unit	Note
		Min	Max		
Power Supply Voltage	VIN5	4.5	5.5	V	(1)
Logic Input Voltage	VDD	-0.3	3.6	V	

Note (1) Permanent damage to the device may occur if maximum values are exceeded. Function operation should be restricted to the conditions described under Normal Operating Conditions.

6

Version 2.1

Issued Date: 22, SEP 2008
Model No.: V260B1　- PN1

Approval

3. ELECTRICAL CHARACTERISTICS

3.1 TFT LCD MODULE

Ta = 25 ± 2 ºC

Parameter		Symbol	Value			Unit	Note
			Min.	Typ.	Max.		
Power Supply Voltage		VIN5	4.5	5.0	5.5	V	
		VDD	3.1	3.3	3.5	V	
Power Supply Current		I5V	-	1000	-	mA	
		I3.3V	-	50	-	mA	
CMOS interface	Input High Threshold Voltage	V_{IH}	2.7	-	3.3	V	
	Input Low Threshold Voltage	V_{IL}	0	-	0.7	V	

3.2 RSDS CHARACTERISTICS

Ta = 25 ± 2 ºC

Item	Symbol	Condition	Value			Unit
			Min	Typ	Max	
RSDS high input Voltage	$V_{DIFFRSDS}$	V_{CMRSDS} = +1.2 V (1)	100	200	-	mV
RSDS low input Voltage	$V_{DIFFRSDS}$	V_{CMRSDS} = +1.2 V (1)	-	-200	-100	mV
RSDS common mode input voltage range	V_{CMRSDS}	$V_{DIFFRSDS}$ = 200mV (2)	0.1	1.2	VDD-1.2	V
RSDS Input leakage current	I_{DL}	$D_{xx}P$, $D_{xx}N$,CLKO ,CLPN	-10	-	10	μA

Note (1) V_{CMRSDS} = (VCLKP + VCLKN)/2 or V_{CMRSDS} = ($VD_{XX}P$ + $VD_{XX}N$)/2

Note (2) $V_{DIFFRSDS}$ = VCLKP - VCLKN or $V_{DIFFRSDS}$ = $VD_{XX}P$ - $VD_{XX}N$

4. BLOCK DIAGRAM

4.1 TFT LCD MODULE

TFT LCD PANEL

(1366x3x768)

X BOARD

↑

RSDS SIGNAL INPUT

Connector Part No.: Starconn 089H45-000000-G2-C (55) or Compatible

7

Version 2.1

Approval

5. INPUT TERMINAL PIN ASSIGNMENT

5.1 TFT LCD MODULE

CN2(X) Connector Pin Assignment

Pin No.	Symbol	Description	Pin No.	Symbol	Description
1	GND	Ground	29	TP1	RSDS data latch
2	NC	No connection	30	POL	polarity invert
3	NC	No connection	31	GND	Ground
4	GND	Ground	32	NC	No connection
5	B2P	RSDS data signal (Blue2)	33	VDD	Logic Power supply: +3.3V
6	B2N	RSDS data signal (Blue2)	34	VDD	Logic Power supply: +3.3V
7	B1P	RSDS data signal (Blue1)	35	VIN5	Power supply: +5V
8	B1N	RSDS data signal (Blue1)	36	VIN5	Power supply: +5V
9	B0P	RSDS data signal (Blue0)	37	VIN5	Power supply: +5V
10	B0N	RSDS data signal (Blue0)	38	STV	Scan driver start pulse
11	G2P	RSDS data signal (Green2)	39	CKV	Scan driver clock
12	G2N	RSDS data signal (Green2)	40	OE	Scan driver output enable
13	G1P	RSDS data signal (Green1)	41	NC	No connection
14	G1N	RSDS data signal (Green1)	42	NC	No connection
15	G0P	RSDS data signal (Green0)	43	GVOFF	3-level power control signal
16	G0N	RSDS data signal (Green0)	44	NC	No connection
17	CLKP	Data driver clock	45	GND	Ground
18	CLKN	Data driver clock			
19	R2P	RSDS data signal (Red2)			
20	R2N	RSDS data signal (Red2)			
21	R1P	RSDS data signal (Red1)			
22	R1N	RSDS data signal (Red1)			
23	R0P	RSDS data signal (Red0)			
24	R0N	RSDS data signal (Red0)			
25	GND	Ground			
26	NC	No connection			
27	NC	No connection			
28	STH	source driver start pulse			

Note (1) CN2 Connector Part No.: HIROSE FH12-45S-0.5SH (55) or Compatible.

Version 2.1

Issued Date: 22, SEP 2008
Model No.: V260B1   - PN1

Approval

5.2 COLOR DATA INPUT ASSIGNMENT

The brightness of each primary color (red, green and blue) is based on the 8-bit gray scale data input for the color. The higher the binary input, the brighter the color. The table below provides the assignment of color versus data input.

Color		Data Signal																	
		Red						Green						Blue					
		R5	R4	R3	R2	R1	R0	G5	G4	G3	G2	G1	G0	B5	B4	B3	B2	B1	B0
Basic Colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Green	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1
	Cyan	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1
	Magenta	1	1	1	1	1	1	0	0	0	0	0	0	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Gray Scale Of Red	Red(0) / Dark	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red(1)	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0
	Red(2)	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Red(61)	1	1	1	1	0	1	0	0	0	0	0	0	0	0	0	0	0	0
	Red(62)	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red(63)	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
Gray Scale Of Green	Green(0) / Dark	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Green(1)	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0
	Green(2)	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Green(61)	0	0	0	0	0	0	1	1	1	1	0	1	0	0	0	0	0	0
	Green(62)	0	0	0	0	0	0	1	1	1	1	1	0	0	0	0	0	0	0
	Green(63)	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
Gray Scale Of Blue	Blue(0) / Dark	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Blue(1)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
	Blue(2)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Blue(61)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	0	1
	Blue(62)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	0
	Blue(63)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1

Note (1) 0: Low Level Voltage, 1: High Level Voltage

9

Version 2.1

Issued Date: 22, SEP 2008
Model No.: V260B1 - PN1

Approval

6. INTERFACE TIMING

6.1 INPUT SIGNAL TIMING SPECIFICATIONS

(a) Timing Spec

	Parameter	Symbol	Condition	Spec			Unit
				Min.	Typ.	Max.	
HD (1)	Clock pulse width	tCLK	-	12.5	-	-	ns
	Clock pulse low period	tCLK(L)	-	5	-	-	ns
	Clock pulse high period	tCLK(H)	-	5	-	-	ns
	Data setup time	tSETUP1	-	4	-	-	ns
	Data hold time	tHOLD1	-	1	-	-	ns
	Start pulse setup time	tSETUP2	-	2	-	-	ns
	Start pulse hold time	tHOLD2	-	2	-	-	ns
	TP1 high period	tTP1(H)	-	15	-	-	CLKP
	Last data CLK to TP1 high	tLAST	-	1	-	-	CLKP
	TP1 high to STH high	tNEXT	-	6	-	-	CLKP
	POL to TP1 setup time	tPOL-TP1	POL toggle to TP1 rising	3	-	-	ns
	TP1 to POL hold time	tTP1-POL	TP1 falling to POL toggle	2	-	-	ns
VD	CKV period	tCKV	-	5	-		μs
	CKV pulse width	tCKVH, tCKVL	50% duty cycle	2	-		μs
	OE pulse width	tWOE	-	1	-		μs
	Data setup time	tSU	-	0.5	-		μs
	Data hold time	tHD	-	0.5	-		μs
	CKV to output delay time	tPD1	CL=300pF	-	-	1	μs
	OE to output delay time	tPD3	CL=300pF	-	-	0.8	μs

Version 2.1

Issued Date: 22, SEP 2008
Model No.: V260B1   - PN1

Approval

(b) Horizontal Timing Chart

11

Version 2.1

Issued Date: 22, SEP 2008
Model No.: V260B1   - PN1

Approval

(c) Vertical Timing Chart

Version 2.1

6.2 POWER ON/OFF SEQUENCE

To prevent a latch-up or DC operation of LCD module, the power on/off sequence should follow the conditions shown in the following diagram.

Power ON/OFF Sequence

Note :

(1) The supply voltage of the external system for the module input should be the same as the definition of Vcc.

(2) Please apply the lamp voltage within the LCD operation range. When the backlight turns on before the LCD operation of the LCD turns off, the display may, instantly, function abnormally.

(3) In case of V_{CC} = off level, please keep the level of input signals on the low or keep a high impedance.

(4) T4 should be measured after the module has been fully discharged between power on/off periods.

(5) Interface signal shall not be kept at high impedance when the power is on.

Version 2.1

Issued Date: 22, SEP 2008
Model No.: V260B1   - PN1

Approval

7. OPTICAL CHARACTERISTICS

7.1 TEST CONDITIONS

Item	Symbol	Value	Unit
Ambient Temperature	Ta	25±2	^{o}C
Ambient Humidity	Ha	50±10	%RH
Supply Voltage	V_{CC}	5.0	V
Input Signal	According to typical value in "3. ELECTRICAL CHARACTERISTICS"		
Lamp Current (High side)	I_{L}	7.5mA ± 0.5	mA
Oscillating Frequency (Inverter)	F_{W}	58±3	KHz
Frame rate		60	Hz

7.2 OPTICAL SPECIFICATIONS

The relative measurement methods of optical characteristics are shown in 7.2. The following items should

be measured under the test conditions described in 7.1 and stable environment shown in Note (5).

Item			Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Color Chromaticity	Red	Rcx		$\theta_x=0°$, $\theta_Y =0°$ Viewing Angle at Normal Direction Standard light source "C"	-	0.650	-	-	(0),(5)
		Rcy				0.328		-	
	Green	Gcx				0.274		-	
		Gcy				0.583		-	
	Blue	Bcx				0.150		-	
		Bcy				0.094		-	
	White	Wcx				0.314		-	
		Wcy				0.331		-	
Center Transmittance			T%	$\theta_x=0°$, $\theta_Y =0°$ with CMO module	-	6.2	-	%	(1),(7)
Contrast Ratio			CR			800	-		(1),(3)
Response Time			T_R	$\theta_x=0°$, $\theta_Y =0°$ with CMO Module@60Hz	-	3	-	ms	(4)
			T_F		-	5	-	ms	
White Variation			δW	$\theta_x=0°$, $\theta_Y =0°$ with CMO module	-	-	1.3	-	(1),(6)
Viewing Angle	Horizontal	θ_x+		CR≥10 With CMO module	-	80	-	Deg.	(1),(2)
		θ_x-			-	80	-		
	Vertical	θ_Y+			-	80	-		
		θ_Y-			-	70	-		

14

Version 2.1

**CHI MEI** OPTOELECTRONICS CORP.

Approval

Note (0) Light source is the standard light source "C" which is defined by CIE and driving voltage are based on suitable gamma voltages. The calculating method is as following :

　1. Measure Module's and BLU's spectrum. White is without signal input and R,G,B are with signal input. BLU(for V260B1-LN1) is supplied by CMO.

　2. Calculate cell's spectrum.

　3. Calculate cell's chromaticity by using the spectrum of standard light source "C".

Note (1) Light source is the BLU which is supplied by CMO and driving voltage are based on suitable gamma voltages.

Note (2) Definition of Viewing Angle (θx, θy):

Viewing angles are measured by EZ-Contrast 160R (Eldim)

Normal

θx = θy = 0º

θy- 　 θy+

θx- = 90º　x-

θx−　θx+

12 o'clock direction

θy+ = 90º

y+

6 o'clock

θy- = 90º　y-

x+　θx+ = 90º

Note (3) Definition of Contrast Ratio (CR):

The contrast ratio can be calculated by the following expression.

Contrast Ratio (CR) = L255 / L0

L255: Luminance of gray level 255

L 0: Luminance of gray level 0

CR = CR (5), where CR (X) is corresponding to the Contrast Ratio of the point X at the figure in

Note (6).

15

Version 2.1

Note (4) Definition of Response Time (T_R, T_F):

Gray Level 255

Gray Level 255

100%
90%

Optical

Response

Gray Level 0

10%
0%

Time

T_R

T_F

Note (5) Measurement Setup:

The LCD module should be stabilized at given temperature for 1 hour to avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting Backlight for 1 hour in a windless room.

LCD Module

LCD Panel

Center of the Screen

Display Color Analyzer
(Minolta CA210)

Light Shield Room

(Ambient Luminance < 2 lux)

16

Approval

Note (6) Definition of White Variation (δW):

Measure the luminance of gray level 255 at 5 points

δW = Maximum [L (1), L (2), L (3), L (4), L (5)] / Minimum [L (1), L (2), L (3), L (4), L (5)]

Horizontal Line

Active Area

Note (7) Definition of Transmittance (T%) :

Module is without signal input.

$$\text{Transmittance} = \frac{\text{Luminance of LCD module}}{\text{Luminance of backlight}} * 100\%$$

17

Version 2.1

Issued Date: 22, SEP 2008
Model No.: V260B1   - PN1

Approval

8. PRECAUTIONS

8.1 ASSEMBLY AND HANDLING PRECAUTIONS

(1) Do not apply rough force such as bending or twisting to the product during assembly.

(2) To assemble backlight or install module into user's system can be only in clean working areas. The dust and oil may cause electrical short or worsen the polarizer.

(3) It's not permitted to have pressure or impulse on the module because the LCD panel will be damaged.

(4) Always follow the correct power sequence when the product is connecting and operating. This can prevent damage to the CMOS LSI chips during latch-up.

(5) Do not pull the I/F connector in or out while the module is operating.

(6) Use a soft dry cloth without chemicals for cleaning, because the surface of polarizer is very soft and easily scratched.

(7) It is dangerous that moisture come into or contacted the product, because moisture may damage the product when it is operating.

(8) High temperature or humidity may reduce the performance of module. Please store this product within the specified storage conditions.

(9) When ambient temperature is lower than 10ºC may reduce the display quality. For example, the response time will become slowly.

8.2 SAFETY PRECAUTIONS

(1) If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth. In case of contact with hands, skin or clothes, it has to be washed away thoroughly with soap.

(2) After the product's end of life, it is not harmful in case of normal operation and storage.

Version 2.1

Issued Date: 22, SEP 2008
Model No.: V260B1   - PN1

Approval

9. PACKAGING

9. Packing

9.1 PACKING SPECIFICATIONS

(1) 15 LCD TV Panels / 1 Box

(2) Box dimensions : 804 (L) X 565 (W) X 363 (H)

(3) Weight : approximately 25 Kg (15 panels per box)

9.2 PACKING METHOD

Figures 9-1 and 9-2 are the packing method

Figure.9-1 Packing Method

Version 2.1

Issued Date: 22, SEP 2008
Model No.: V260B1   - PN1

Approval

Sea Transportation

Corner Protector:L1650*50*50mm
            L800*50*50mm
Pallet:L1150*W840*H140mm
Pallet Stack:L1150*W840*H1960mm
Gross:265kg

Air Transportation

Corner Protector:L1250*50*50mm
            L800*50*50mm
Pallet:L1150*W840*H140mm
Pallet Stack:L1150*W840*H1597mm
Gross:215kg

Figure.9-2 Packing Method

10. REGULATORY STANDARDS

10.1 SAFETY

Regulatory	Item	Standard
Information Technology equipment	UL	UL 60950-1: 2003
	cUL	CAN/CSA C22.2 No.60950-1-03
	CB	IEC 60950-1:2001
Audio/Video Apparatus	UL	UL 60065: 2003
	cUL	CAN/CSA C22.2 No.60065-03
	CB	IEC 60065:2001

Version 2.1

Issued Date: 22, SEP 2008
Model No.: V260B1　- PN1

Approval

11. DEFINITION OF LABELS

11.1 OPEN CELL LABEL

The barcode nameplate is pasted on each open cell as illustration for CMO internal control.

V260B1-PN1

XXXXXXXXXXXXXX

V260B1-PN1 Rev.

XXXXXXXXXXXXXX

11.2 CARTON LABEL

The barcode nameplate is pasted on each box as illustration, and its definitions are as following explanation

P.O. NO._____

Parts ID._____

Carton ID._____ Quantities _15_

XXXXXXXXXXXXXX

Made in Taiwan

P.O. NO._____

Parts ID._____

Carton ID._____ Quantities _15_

XXXXXXXXXXXXXX

Made in China

(a) Model Name: V260B1– PN1

(b) Carton ID: CMO internal control

(c) Quantities: 15

21

Version 2.1

Issued Date: 22, SEP 2008
Model No.: V260B1　- PN1

Approval

12. MECHANICAL DRAWING

22

Version 2.1